

PRODUCT Catalog



Catagories



Saws

р8



PTFE



Pipe Tape





Clamps

Catagories



Gloves

p20



Paint

p21



Earplugs

p22



Eye Protection

p23



RHX Guages

RHX's durable, long-lasting liquid filled gauges perform in all types of difficult environments, including areas with extreme heat, pulsation and vibration. Our state of the art gauges are designed with a full scale accuracy of +/- 1.2%

Property	Test Method
Dial	2.5" (63mm) white aluminum with black markings
Case	AISI 304 SS
Lens	Polycarbonate
Ring	AISI 304 SS, Crimp-On
Socket	Brass
Connection	1/4" NPT lower mount
Fill Liquid	Glycerin
Bourdon Tube	2.5" (63mm), Phosphore bronze or lead free phosphor bronze C or coil shaped for brass socket, AISI 316 SS C or Coil shaped for 316 SS socket
Movement	Brass
Pointer	Aluminum, anodized black
Welding	Brass: Silver Alloy, 316SS: TIG
Over-Pressure Limit	25% for pressure, up to 1,450 psi (9,998kPa), 15% for pressures over 1,500 psi (10,342 kPa)
Gasket	Silicone rubber for socket; EPDM for lens, filling plug and blow-out-vent
Fill Plug	EPDM
Lens Ring Gasket	Silicone Rubber
Working Pressure	Maximum 75% of full scale value
Ambient/Proccess Temp.	Glycerin Filled: -4°F to 150° F (-20°C to 65°C)
Accuracy	± 1.2% of full scale
Enclosure Rating	IP65

Liquid Filled Gauges























Dry Gauges
















Air Test and Water Gauges













RHX PVC/ABS saws allows for easy cutting though PVC, woods, metals, and plastics. The comfort rubber handle provides added grip and durability during use.

Product Details

- · 12" or 18" PVC/ABS Saw
- · Aluminum Handle Saw with Comfort Rubber Grip
- · 12" or 18" Blade
- Suitable for Plywood, Asbestos, Plastics, Hardboard, Metals, Wood, Plastic and Foam Core Pipe

Saws and Replacement Blades













RXH PTFE TAPE

WHITE PTFE THREAD SEAL TAPE:

For all industrial applications. Made from 100% virgin PTFE. No pigments, no additives. May be used on all applications including water, oil, chemical, medical, and food processing where non-contamination standards are high. Exceeds MIL Spec T-27730A.Temperature range of -450°F to +550°F. Available in a variety of sizes. Not for oxygen use.

BLUE PTFE THREAD SEAL TAPE:

For all industrial applications. Made from 99.5% virgin PTFE. .5% Blue Pigment. May be used on all applications including water, oil, chemical, medical, and food processing where non-contamination standards are high Temperature range of -450°F to +550°F. Available in a variety of sizes. Not for oxygen use.

White PTFE Size	Density	Thickness
1/2" x 260" 0.4	0.0035"	+/- 0.0005"
1/2" x 520" 0.4	0.0035"	+/- 0.0005"
3/4" x 520" 0.4	0.0035"	+/- 0.0005"
1" x 520" 0.4	0.0035"	+/- 0.0005"

Blue Steel Size	Density	Thickness
1/2" x 260" 0.8	0.0035"	+/- 0.0005"
1/2" x 520" 0.8	0.0035"	+/- 0.0005"
3/4" x 520" 0.8	0.0035"	+/- 0.0005"
1" x 520" 0.8	0.0035"	+/- 0.0005"

PTFE Tape and Blue Steel Tape

















PIPE WRAP TAPE

PREMIUM GRADE, STRONG ADHESION, WATERPROOF, NON-CORROSIVE

TAKLUR FRICK: 1X10 FAVT



RXH PIPE TAPE

RHX "UPC Approved" Pipe Wrap Tape is a physical barrier that is moisture proof, inert and non-conducting. Whether the need is to protect overhead piping in industrial applications, exposed pipe anywhere, or direct burial piping, this tape gives a completely uniform coating all around. It is easy to apply by hand with no special tools or equipment.

PVC Pipe Tape Duct Tape and Caution Tape











Cloth Duct Tape and Caution Tape



Cloth duct tape is polyethylene coated cloth backing with release material, single coated with a high performance sensitive adhesive.

FEATURES:

Polyethylene plastic backing is for waterproofing. Shelf life: one year in the original packing carton when stored $23^{\circ}\text{C}\times65\%\text{RH}$

Cloth middle layer facilitates tearing by hand. (Glossy) The adhesive holds good peel force, tack, stretching resistance, aging resistance and weatherability.

APPLICATIONS:

- Sealing duct work.
- General purpose for packing and enlacing.
- Carpet joint seaming.
- Masking and protection in painting.

Thickness	Adhesive	Tack #	Tensile strength N/25mm	1800 peeling N/25mm	Elongation at break	Temperature Resistance °C	
0.23mm	Hot Melt	≥12	≥60	≥12	5%	80	



RHX's Caution/ Barricade Tape is the best choice for marking hazardous areas. Not only is our Caution Tape highly visible and completely reusable, but because it is 3 mil thick it does not easily fold making readability much clearer. Each message is printed in English and Spanish with bold black ink on durable yellow polyethylene. RHX caution tape is available in two sizes: 3inx300ft and 3inX1000ft.

APPLICATIONS:

• Simply unroll the amount of tape needed to block off areas that offer a potential hazard. Re-roll the unused amount of tape and store. To attach the tape, simply wrap or staple.



Complete a variety of clean up using a RHX 100 % Cotton Terry Cloth Towel. The soft material is absorbent to soak up water and other liquids and safe to use on many surfaces and finishes. The cotton towel comes in a 12-pack and is reusable and hemmed for durability.





These durable, UPC approved stainless steel hose clamps are ideal for use in a broad range of projects and applications. Screw, band and housing are comprised of 300 series stainless steel.

300 Stainless Clamps


















































RHX-TBOLT-Size 4 Belt Width 1.02" Coverage 4" - 4.33"



RHX-18UL1-51Ze 6 Belt Width 1.02" Coverage 5.58" - 6.33"



RHX-TBOLT-Size 8 Belt Width 1.02" Coverage 7.91" - 8.33"





RHX Gloves

RHX Touchscreen

Compatable gloves provide enhanced safety, durability, dexterity and great grip in wet, oily, or dry conditions.



Product Details

RHX Gloves are designed with a protective lightweight Nitrile coated palm accompanied by Newfoam Technology finish allowing access to use touchscreen devices without removing gloves.

- Reinforced thumb crotch increases abradion resistance
- Knitwrist cuff offers users a secure comfortable fit

PAINT AND PAINTING SUPPLIES

WATER-BASED MARKING PAINTS (12 per case)				
APWA	TallBoy™ (22 oz.)	17 oz.		
APWA High-Vis Yellow	T03921004	A03921004		
APWA Red	T03911004	A03911004		
APWA White	T03901004	A03901004		
APWA Utility Yellow	T03801004	A03801004		
APWA Blue	T03903004	A03903004		
APWA Orange		A03905004		
APWA Green		A03904004		
APWA Clear*		A03500		
APWA Black		A03923004		



Marking Wands · Use for easy stenciling or line touch-ups · Durable construction · 34" length for convenient operation K07095 Spotter Handheld Wand (12" Length) K07096 Wheeler Handheld Wand (34" Length) K07094000 Handheld Wand with Flag Holder (34" Length) Line-Up Striping Wand (34" Length) K08360000 Snap & Spray™ K07091000 Can Holster K08000000 Case Pack: 1



Earplugs

RHX-35DP-BP Earplugs are designed to be reusable or disposable, while preventing noise induced hearing loss. These cordless hearing protection devices reduce noise energy from reaching and causing damage to the inner ear. They are simple to use, less expensive than muffs, and often more comfortable to wear when in hot or damp work areas.



Product Details

FEATURES

- EN 352-2:2002 & ANSI Certified product.
- Individually packed for convenience
- •Universal fit to suit most ear canals
- •Optimal expansion rate for easy fitting
- Hi Visibility color for easy wearer identification

Safety Glasses

Pro Series Glasses

For workers who want style and protection, the RHX Pro Safety Glasses with Side Shields deliver outstanding peripheral vision and impact protection in a simple design.

FEATURES:

Classic, Nylon frame & TPEE leg with rubber design promotes worker compliance. Low base curve frame and clear side shields provide excellent peripheral vision and protection. Scratch resistant hard coat Anti-Fog lenses in clear and smoke offer long lasting protection.



APPLICATIONS:

- Woodworking
- **Painting**
- Assembly
- Sanding
- Cleaning
- Machine Operation
- Available in Clear or Smoke











Contact Us

Address:

8290 BELVEDERE AVE #100 Sacramento, Ca. 95826

Email:

info@savkosales.com